

# 700 Series Pushbuttons

#### Overview

Schlage Pushbuttons are used to control the ingress and/or egress of a door. The 700 Series Pushbuttons are easy to install and operate.

Schlage 700 Series Entry Level Pushbuttons are designed to meet commercial applications. Use with egress swinging or sliding doors that are electrically or electronically locked. 700 Series Entry Level Pushbuttons are available for single gang and narrow stile applications. The 709 model, includes backlit buttons with "PUSH TO EXIT" or Handicap Symbol to meet ADA requirements.



### **Features and Benefits**

- · Single gang and narrow stile
- · Standard stainless steel
- · Momentary action (standard)
- Options include LEDs, alternate action maintained (AA)



700 Specifications	
701 Pushbutton	
Contact Ratings	5 amps @ 250 VAC
Wire Leads	20 awg – 6" long
709 Pushbutton	
Contact Ratings	10 amps @ 250 VAC
Wire Leads	20 awg – 8" long
Input requirements with LED option	
Voltage	12/24 VDC
Current Draw	30 mA
Wire Leads	24 awg – 6" long
Input requirements with ILL option	
Voltage	12 VDC for 709 series only 24 VDC for 701/709 series

#### **ORDERING INFORMATION**

701RD 7/8" Red Mushroom Button701BK 7/8" Black Mushroom Button

701RD EX | 5/8" Red Button - Engraved "PUSH TO EXIT"

701RD EX ILL | 5/8" Red Button - Illuminated "PUSH TO EXIT"

709RD EX ILL | 2" Red Square - Illuminated "PUSH TO EXIT"

709GR EX ILL | 2" Green Square - Illuminated "PUSH TO EXIT"

709BLH ILL | 2" Blue Square - Illuminated Handicapped Symbol

## **OPTIONS**

**L2** Two LEDs, red and green, dual voltage

**AA** Alternate Action – Maintained (not available for 709 models)

**NS** Narrow Stile plate (not available for 709 models)

